



Product Data Sheet



Berm Builder Plus

Drive-over barrier provides heavy-duty custom containment

- + Create permanent containment on concrete, asphalt and most sealed areas.
- + Heavy-duty, 40-ounce, vinyl-coated fabric can withstand traffic from trucks, forklifts and other vehicles.
- + Open-cell foam core compresses to approximately 1/4" when driven over and springs back to shape when vehicles pass.
- + Secures to the floor with sealant (not included) and is reinforced with pre drilled aluminum mounting strips (included) and steel anchors (included).
- + Can be used with standard Ultra-Berm Builder.



Part#	Description	Dimensions in. (mm)	Qty	Weight lbs. (kg)
2" Model				
8671	Straight Section	150 x 5.5 x 2 (3,810 x 139.7 x 50.8)	1/box	11.50 (5.22)
4" Model				
8634	Straight Section	144 x 6 x 4 (3657.6 x 152.4 x 101.6)	1/box	14.0 (6.4)
6" Model				
8637	Straight Section	144 x 8 x 6 (3657.6 x 203.2 x 152.4)	1/box	21.0 (9.5)

Material Specifications

Base Fabric (100% Polyester) 1300D x 1300D / 31 x 31

Weight (FS-191-5041) 40 oz./yd²

Tensile Strength (Grab)
(FS-191-5100) 920 lbs x 870 lbs

Tensile Strength (Strip)
(FS-191-5102) 685 lbs x 655 lbs

Tear Strength (Tongue)
(FS-191-5134) 715 lbs x 695 lbs

Adhesion Strength
(FS-191-5970) 11 x 11 lbs / inch

Abrasion Resistance
(FS-191-5306) 685 cycles

Hydrostatic Resistance
(FS-191-5512) At least 600 lbs / inch²

U.V. Resistance
(Weather-O-Meter) Not excessive fading after 300 HRS

Cold Crack Resistance
(FS-191-5874) -40° F

High Temperature Resistance
(FS-191-5872) 180° F (Does not Block)