



Product Data Sheet

Item Number: 2126/2127/2130/2131/2132/2133/2134/2135/2136/2137/2124/2125

Item Name: Drain Seals

Item #	Color	Misc. Features	Amount	Length	Width	Height	Weight
2126	Safety Orange	Square	1 Each	18" (458mm)	18" (458mm)	.375" (9.5mm)	5 Lbs. (2.5Kg)
2127	Safety Orange	Square	1 Each	24" (610mm)	24" (610mm)	.375" (9.5mm)	8 Lbs. (3.5Kg)
2130	Safety Orange	Square	1 Each	36" (915mm)	36" (915mm)	.375" (9.5mm)	20 Lbs. (9 Kg)
2131	Safety Orange	Square	1 Each	42" (1067mm)	42" (1067mm)	.375" (9.5mm)	23 Lbs. (10.5 Kg)
2132	Safety Orange	Square	1 Each	48" (1220mm)	48" (1220mm)	.375" (9.5mm)	36 Lbs. (17 Kg)
2133	Safety Orange	Square	1 Each	54" (1372mm)	54" (1372mm)	.375" (9.5mm)	41 Lbs. (18.5Kg)
2134	Safety Orange	Circular	1 Each	12" Diameter (305mm)		.375" (9.5mm)	3 Lbs. (1.5 Kg)
2135	Safety Orange	Circular	1 Each	20" Diameter (508mm)		.375" (9.5mm)	6 Lbs. (3 Kg)
2136	Safety Orange	Circular	1 Each	30" Diameter (762mm)		.375" (9.5mm)	11 Lbs. (5 Kg)
2137	Safety Orange	Circular	1 Each	42" Diameter (1067mm)		.375" (9.5mm)	19 Lbs. (9 Kg)
2124	Safety Orange	Rectangular	1 Each	18" (458mm)	58" (1474mm)	.375" (9.5mm)	16 Lbs. (7 Kg)
2125	Safety Orange	Rectangular	1 Each	36" (915mm)	58" (1474mm)	.375" (9.5mm)	26 Lbs. (12 Kg)

Description: A non-absorbing urethane pad that forms a temporary bond with drains to stop leaks from entering the drain.

Application: For use in response to machine leaks and small chemical spills. They can be quickly deployed to seal floor or storm drains until the spill or leak can be cleaned in accordance with local and state regulations.

Product Features: The Drain Seal is an essential part of your spill response kit that can be quickly deployed to seal drains and prevent spills or leaks from going down the drain.

- Reinforced mesh is sandwiched between layers of polyurethane – increases durability and resistance to tearing.
- Unique, urethane construction allows the pad to deform and seal off most drains – temporarily seals to any smooth surface.
- A valuable addition to any emergency response plan, spill kit, or stormwater management program.
- Unlike some alternative products, BOTH sides will quickly seal drains – there is no specified top or bottom.
- Flexible non-absorbing material with reinforced, tear resistant mesh.
- Resists oil, water and most aggressive chemicals, cleans with soap and water.
- NOT intended for long term outdoor use (more than 2 hours), as UV exposure and/or heat for extended periods of time can degrade the product.

Composition: 100% polyurethane.

Material Specifications:

Specification	Value	
Style	Pad (Square/ Circular/ Rectangular)	
Color	Safety Orange	
Intended For	Storm and Floor Drains	
Max Liquid Temp Exposure	225°F for up to 30 minutes	107.2°C for up to 30 minutes
Storage Temp Range	0°- 120°F	-17.7° - 48.8°C
Temperature Limit	0°- 160°F	-17.7° - 71.1°C
Sold As	1 each	
Composition	Polyurethane	